

LONG REACH ATTACHMENT


SK210_{LC}

SK210LC-9

SK260_{LC}

SK260LC-9

Lifting Capacities



Rating over front



Rating over side or 360 degrees

A – Reach from swing centerline for bucket hook

B – Bucket hook height above/below ground

C – Lifting capacities in pounds

SK210LC 50ft Boom; 28'8", Arm; 20'10", Bucket; 06cu.yd. SAE heaped 820 lbs, Counterweight; 12,800 lbs, Shoe; 31.5"

B	A	5'		10'		15'		20'		25'		30'		35'		40'		45'		At Max. Reach		Radius				
		Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating					
40'	lb																					* 1,630	* 1,630	33'10"		
35'	lb																						* 1,460	* 1,460	38'3"	
30'	lb																						* 1,360	* 1,360	41'7"	
25'	lb																						* 1,320	* 1,320	44'2"	
20'	lb																						* 1,320	* 1,320	46'0"	
15'	lb																						* 1,350	* 1,350	47'2"	
10'	lb																						* 1,420	* 1,420	47'11"	
5'	lb																						* 1,530	* 1,530	48'0"	
GL	lb																						* 1,680	* 1,680	47'8"	
-5'	lb	* 4,390	* 4,390	* 6,370	* 6,370	* 11,700	* 11,700	* 13,380	8,650	* 10,200	6,320	* 8,200	4,810	6,530	3,750	5,280	2,960	* 3,840	2,350	* 1,900	* 1,900				46'9"	
-10'	lb	* 6,280	* 6,280	* 8,190	* 8,190	* 12,750	12,660	* 13,670	8,290	10,460	6,010	7,990	4,580	6,350	3,580	5,170	2,850	* 2,560	2,300	* 2,210	* 2,210				45'3"	
-15'	lb	* 8,250	* 8,250	* 10,300	* 10,300	* 14,760	12,660	* 13,460	8,170	10,310	5,870	7,870	4,460	6,260	3,500	5,130	2,810						* 2,670	2,500		43'1"
-20'	lb	* 10,360	* 10,360	* 12,730	* 12,730	* 16,890	12,870	* 12,750	8,230	* 10,030	5,870	7,860	4,460	6,280	3,510	* 3,860	2,880						* 3,370	2,860		40'3"
-25'	lb	* 12,690	* 12,690	* 15,590	* 15,590	* 14,920	13,270	* 11,470	8,450	* 9,080	6,020	* 7,270	4,580	* 5,690	3,660								* 4,580	3,470		36'6"
-30'	lb			* 16,130	* 16,130	* 12,030	* 12,030	* 9,410	8,850	* 7,410	6,330	* 5,640	4,880										* 5,090	4,580		31'6"
-35'	lb					* 7,700	* 7,700	* 6,020	* 6,020														* 4,460	* 4,460		24'5"

SK260LC 60ft Boom; 33'11", Arm; 27'1", Bucket; 05cu.yd. SAE heaped 770 lbs, Counterweight; 15,400 lbs, Shoe; 31.5"

B	A	5'		10'		15'		20'		25'		30'		35'		40'		45'		50'		55'		At Max. Reach		Radius					
		Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating		Rating				
40'	lb																									* 1,370	* 1,370	45'8"			
35'	lb																										* 1,320	* 1,320	49'0"		
30'	lb																										* 1,300	* 1,300	51'7"		
25'	lb																										* 1,310	* 1,310	53'8"		
20'	lb																										* 1,350	* 1,350	55'2"		
15'	lb																										* 1,420	* 1,420	56'3"		
10'	lb																										* 1,520	* 1,520	56'9"		
5'	lb																										* 1,650	* 1,650	56'11"		
GL	lb	* 3,070	* 3,070	* 5,660	* 5,660	12,570	12,570	* 11,850	11,850	* 8,900	8,900	* 7,130	6,920	* 5,980	5,430	* 5,170	4,320	4,590	3,450	4,160	2,760	* 2,840	2,190	* 1,820	* 1,820		56'7"				
-5'	lb	* 4,450	* 4,450	* 6,270	* 6,270	10,720	10,720	* 13,180	11,030	* 9,880	8,170	* 7,850	6,320	6,510	5,000	* 5,580	4,000	4,900	3,220	* 4,380	2,600	2,650	2,090	* 2,040	2,020		55'10"				
-10'	lb	* 5,810	* 5,810	* 7,400	* 7,400	10,910	10,910	14,030	10,330	10,600	7,600	* 8,420	5,870	* 6,950	4,660	* 5,920	3,750	5,150	3,040	4,520	2,470					* 2,340	2,050	54'7"			
-15'	lb	* 7,200	* 7,200	* 8,750	* 8,750	11,890	11,890	14,470	9,970	11,040	7,250	* 8,810	5,580	* 7,280	4,420	* 6,170	3,570	5,250	2,910	4,440	2,390					* 2,750	2,150	52'10"			
-20'	lb	* 8,630	* 8,630	10,260	10,260	13,310	13,310	14,540	9,870	11,230	7,100	* 9,010	5,420	* 7,450	4,290	6,180	3,470	5,180	2,840	* 3,930	2,360					* 3,320	2,330	50'6"			
-25'	lb	* 10,120	* 10,120	11,910	11,910	15,070	15,070	14,270	9,950	11,140	7,100	* 9,000	5,390	* 7,450	4,260	6,170	3,450	5,190	2,850								* 4,180	2,610	47'7"		
-30'	lb	* 11,690	* 11,690	13,720	13,720	17,180	16,130	13,620	10,200	10,740	7,240	* 8,720	5,490	* 7,220	4,330	* 6,030	3,530											* 5,230	3,080	43'11"	
-35'	lb	* 13,330	13,330	15,690	15,690	16,460	16,460	12,540	10,600	* 9,960	7,520	* 8,100	5,700	* 6,660	4,530													* 5,610	3,840	39'3"	
-40'	lb			* 17,810	* 17,810	14,040	14,040	* 10,840	10,840	* 8,650	7,970	* 6,970	6,080															* 6,050	5,280	33'2"	
-45'	lb																												* 6,550	* 6,550	24'7"

Notes:

- Do not attempt to lift or hold any load that is greater than these lift capacities at their specified lift point radius and heights. Weight of all accessories must be deducted from the above lift capacities.
- Lift capacities are based on machine standing on level, firm, and uniform ground. User must make allowance for job conditions such as soft or uneven ground, out of level conditions, side loads, sudden stopping of loads, hazardous conditions, experience of personnel, etc.
- Bucket lift hook is defined as lift point.
- The above lifting capacities are in compliance with SAE J/ISO 10567. They do not exceed 87 % of hydraulic lifting capacity or 75 % of tipping load. Lifting capacities marked with an asterisk (*) are limited by hydraulic capacity rather than tipping load.
- Operator should be fully acquainted with the Operator's and Maintenance Instructions before operating this machine. Rules for safe operation of equipment should be adhered to at all times.
- Lift capacities apply to only machines as originally manufactured and normally equipped by KOBELCO CONSTRUCTION MACHINERY CO., LTD.

Note: This catalog may contain attachments and optional equipment that are not available in your area. And it may contain photographs of machines with specifications that differ from those of machines sold in your areas. Please consult your nearest KOBELCO distributor for those items you require. Due to our policy of continuous product improvements all designs and specifications are subject to change without advance notice. Copyright by **KOBELCO CONSTRUCTION MACHINERY CO., LTD.** No part of this catalog may be reproduced in any manner without notice.

KOBELCO CONSTRUCTION MACHINERY U.S.A. INC.

4690 World Houston Parkway Houston, TX 77032
<http://www.kobelco-usa.com/>

Inquiries To: